

13.56 MHz Contactless – Credentials

									
MIFARE® Card	MIFARE® / HID Prox Combo Card	MIFARE® / Indala® Prox Combo Card	DESFire® Card	DESFire® / HID Prox Combo Card	DESFire® / Indala® Prox Combo Card	MIFARE® Keyfob	DESFire® Keyfob	MIFARE® Adhesive Tag	DESFire® Adhesive Tag
I430: PVC 1k Card	I431: PVC 1k Card	FPMXI: PVC 1k Card	I450: PVC Card	I451: PVC Card	FPDXI: PVC Card	I434: 1k Keyfob	I454	I435: 1k Tag	I455
I440: PVC 4k Card	I441: PVC 4k Card	FPMXX: Composite PET/PVC 1k Card	I456: Composite PET/PVC Card	I457: Composite PET/PVC Card	FPDXX: Composite PET/PVC Card	I444: 4k Keyfob		I445: 4k Tag	
I436: Composite PET/PVC 1k Card	I437: Composite PET/PVC 1k Card								
I446: Composite PET/PVC 4k Card	I447: Composite PET/PVC 4k Card								
Up to 4"			N/A			Up to 2"	N/A	Up to 2"	N/A
N/A			Up to 4"			N/A	Up to 2"	N/A	Up to 2"
N/A	Up to 4.5"	N/A		Up to 4.5"	N/A				
N/A		Up to 4.5"		N/A		Up to 4.5"		N/A	
1k Byte (8,192 bits) or 4k Bytes (32,768 bits)		4k Bytes (32,768 bits)			1k Byte (8,192 bits) or 4k Bytes (32,768 bits)		4k Bytes (32,768 bits)	1k Byte (8,192 bits) or 4k Bytes (32,768 bits)	4k Bytes (32,768 bits)
No	Yes	No	Yes			No			
Yes						No		Yes	
No									
Optional						No			
Yes						No			
Vertical optional						Key Ring Hole		No	
Yes						No			
Lifetime									

* Dependent upon installation conditions.

** Some types of printing processes can take these credentials out of ISO compliance for thickness. Consult factory for more information.